



XTS 10W60

DESCRIPTION

Fully synthetic high-performance engine oil, based on a PAO technology, for petrol and diesel engines, turbo-charged or not. It extends the drain intervals and provides an excellent protection at different temperatures and engine speeds.

APPLICATION

Bardahl XTS 10w60 can be used all year long. Adapted viscosity at low and high temperature. Extends the oil drain interval.

SPECIFICATIONS

This product offers the following performance level:

ACEA	A3/B4
API	SN / CF

PROPERTIES

- ✓ Offers a stable viscosity and a high viscosity index,
- ✓ Makes cold start easier,
- ✓ Offers a good resistance to oxidation,
- ✓ Provides a very good resistance against « shearing »,
- ✓ Forms a lubricating film at high temperature,
- ✓ Offers excellent dispersion and detergency properties,
- ✓ Contains strong anti-corrosion, anti-wear and anti-foam additives.





TECHNICAL DATA

Density at 15°C	Kg/l	0,854
Viscosity at -30°C	mPa.s	6190
Viscosity at 40°C	mm ² /s	163,3
Viscosity at 100°C	mm ² /s	23,3
Viscosity Index		173
Flash point COC, °C	°C	224
Pour point, °C	°C	-39
TBN alcalinity	mgKOH/g	10,3
Sulphated ash contents	%	1,33

The information contained in this sheet is provided for reference only. Because of continual product development, changes may occur without prior notice. No liability for damages caused by the incompleteness or incorrectness will be accepted.

RECOMMENDATIONS

Handling : any safety information related to the handling and use of this product are gathered in the Safety Data Sheet.

Always check the manufacturer car manual before use.

Storage : it is recommended to use the product within 60 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

REFERENCES & AVAILABILITIES

36251	12 x 1 L
36252	4 x 4 L
36253	3 x 5 L
36258	20 L
36254	60 L





TECHNICAL DATA SHEET
V102020

36257	205 L
-------	-------

