



XTC

SCOOTER C60

FULLY SYNTHETIC SPECIAL OIL

Product Data Sheet

Premium Performance lubricant, completely synthetic, specific for 4-stroke Scooter and Maxi-Scooter engines, air or liquid cooled.

Superior Performance – Total Protection

Bardahl advanced technology, thanks to the exclusive Polar Plus + Fullerene formula and the 4-stroke motorcycle engines “ad hoc” additivation, **MCO Tailored Chemistry System**, provides total engine protection allowing greater efficiency and power. Bardahl lubricants ensure significantly higher performance than conventional oils.

- Counteracts the formation of deposits for maximum engine cleanliness
- Suitable for both urban “stop and go” use and long distances
- Ensures top lubrication efficiency even under high stress conditions
- Formulated with special polymers with very high resistance – Radial Polymer Structure
- 100% Synthetic Formula

PERFORMANCE LEVEL

API SN / JASO MA-MA2
SAE 5W-40

CHEMICAL-PHYSICAL CHARACTERISTICS

SAE	Viscosity 40°C cSt	Viscosity 100°C cSt	Density 15°C kg/l	Viscosity Index	Flash Point	Pour Point	T.B.N. mg KOH/g
5W-40	87,5	14,2	0,854	169	212	-45	8

Values mentioned in this table are indicative and variable within certain tolerances

STORAGE

Store in the original closed packaging, maintaining it indoors, protected from moisture, direct exposure to sunlight and weather conditions. Avoid continuous and excessive temperature changes.