



# XTS 5W30

## DESCRIPTION

Fully synthetic engine oil formulated with last generation performance additives to reduce friction, eliminate sludge and optimize fuel consumption. Offers a good general protection of the engine.

## APPLICATION

**Bardahl XTS 5w30** has been specially formulated to lubricate petrol and diesel engines, equipped or not with a turbo, of passenger cars and delivery vans. It is particularly suitable for modern FORD engines but also meets the requirements of the former M2C 913-A, B and C specification levels.

## SPECIFICATIONS

This product offers the following performance level:

ACEA	A5/B5 A1/B1
API	SL/CF
FORD	WSS-M2C 913-D
RENAULT	RN0700
JAGUAR - LAND ROVER	STJLR.03.5003

## PROPERTIES

- ✓ Avoids fuel over-consumption,
- ✓ Offers a stable viscosity and a high viscosity index,
- ✓ Provides an excellent resistance against « shearing »,
- ✓ Is highly resistant against oxidation,
- ✓ Offers excellent dispersion and detergency properties,
- ✓ Forms a lubricating film at high temperature,
- ✓ Makes cold start easier,
- ✓ Contains strong anti-corrosion, anti-wear and anti-foam additives.



## TECHNICAL DATA

Density at 15°C	Kg/l	0,845
Viscosity at -35°C	mPa.s	3890
Viscosity at 40°C	mm <sup>2</sup> /s	54,5
Viscosity at 100°C	mm <sup>2</sup> /s	9,9
Viscosity Index		170
Flash point COC, °C	°C	220
Pour point, °C	°C	-39
TBN Alcalinity	mgKOH/g	10,1
Sulphated Ash contents	%	1,09

The information contained in this sheet is provided for reference only. Because of continual product development, changes may occur without prior notice. No liability for damages caused by the incompleteness or incorrectness will be accepted.

## RECOMMENDATIONS

**Handling :** any safety information related to the handling and use of this product are gathered in the Safety Data Sheet.

Always check the manufacturer car manual before use.

**Storage :** it is recommended to use the product within 60 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

## REFERENCES & AVAILABILITIES

36541	12 x 1 L
36542	4 x 4 L
36543	3 x 5 L
36548	1 x 20 L
36544	1 x 60 L
36547	1 x 205 L