



XTC 10W40

DESCRIPTION

High performance, semi synthetic motor oil for petrol and diesel engines, turbo-charged or not. This engine oil is suitable for extended oil drain intervals. Excellent protection at cold start and at different temperatures It offers an excellent protection at cold start and at any engine temperature.

APPLICATION

Bardahl XTC 10w40 can be used all year long and in the most difficult operating conditions. Offers a good fluidity at low temperature.

SPECIFICATIONS

This product offers the following performance level:

ACEA	A3/B4
API	SN / CF
VW	501.01 / 505.00
MB	229.1
RENAULT	RN 0700

PROPERTIES

- ✓ Offers a stable viscosity,
- ✓ Makes cold start easier,
- ✓ Provides a good resistance to oxidation.





TECHNICAL DATA

Density at 15°C	Kg/l	0,868
Viscosity at -25°C	cP	6500
Viscosity at 40°C	mm ² /s	95
Viscosity at 100°C	mm ² /s	14,2
Viscosity Index		152
Pour point, °C	°C	-39
TBN alkalinity	mgKOH/g	10,3
Sulphated ash contents	%	1,3

The information contained in this sheet is provided for reference only. Because of continual product development, changes may occur without prior notice. No liability for damages caused by the incompleteness or incorrectness will be accepted.

RECOMMENDATIONS

Handling : any safety information related to the handling and use of this product are gathered in the Safety Data Sheet.

Always check the manufacturer car manual before use.

Storage : it is recommended to use the product within 60 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

REFERENCES & AVAILABILITIES

36241	12 x 1 L
36242	4 x 4 L
36243	3 x 5 L
36248	20 L
36244	60 L
36247	205 L

